

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 1 083 047 A1**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
14.03.2001 Bulletin 2001/11

(51) Int Cl.<sup>7</sup>: **B41F 31/04, B41F 31/12**

(21) Application number: **00250295.3**

(22) Date of filing: **05.09.2000**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• Tomita, Toshikazu, Toride Plant, Komori Corp.  
Toride-shi, Ibaragi (JP)  
• Hama, Teruhiko, Japan Printing Academy  
Tokyo 112-0002 (JP)


(30) Priority: **07.09.1999 JP 25269299**

(74) Representative: **Patentanwälte Wenzel & Kalkoff  
Grubessallee 26  
22143 Hamburg (DE)**

(71) Applicant: **Komori Corporation  
Sumida-ku Tokyo (JP)**

(54) **Method and apparatus for adjusting ink supply amount for multicolor printing press**

(57) In an ink supply amount adjusting method for this printing machine, reference opening amounts of ink fountain keys in units of ink colors are obtained in accordance with image area ratios of respective areas, corresponding to the ink fountain keys, of a plate by following a relationship between an image area ratio and opening amounts of the ink fountain keys, the relationship being preset to be common to the respective ink colors. The obtained reference opening amounts are uniformly corrected with correction values preset in units of ink colors, thereby obtaining preset values of the opening amounts of the ink fountain keys in units of ink colors. An ink supply amount adjusting apparatus is also disclosed.



**FIG. 3**

**EP 1 083 047 A1**

## Description

### Background of the Invention

[0001] The present invention relates to a method and apparatus for adjusting the ink supply amount for a multicolor printing press, which adjust the amount of ink to be supplied to a plate by adjusting setting of the opening amount of an ink fountain key and the feed rate (rotation amount) of an ink fountain roller.

[0002] A four-color rotary printing press shown in Fig. 18 has printing units 9-1 to 9-4 provided for four ink colors. An ink supply unit shown in Fig. 17 is provided in each of the printing units 9-1 to 9-4.

[0003] The ink supply unit shown in Fig. 17 has an ink fountain 1, ink 2 stored in the ink fountain 1, an ink fountain roller 3, a plurality of ink fountain keys 4 (4-1 to 4-n) aligned in the axial direction of the ink fountain roller 3, an ink ductor roller 5, an ink roller group 6, a plate 7 and a plate cylinder 8.

[0004] In the printing press having the above arrangement, the amount of ink to be supplied from the ink fountain 1 to the ink fountain roller 3 is adjusted by adjusting the opening amounts of the ink fountain keys 4. The amount of ink to be supplied from the ink fountain roller 3 to the plate 7 through the ink roller group 6 is adjusted by adjusting the feed rate (rotation amount) of the ink fountain roller 3. A print sheet is printed with the ink finally supplied to the plate 7.

[0005] The opening amount of each ink fountain key 4 is set in accordance with the image area ratio of each one of areas corresponding to the ink fountain keys 4 of the plate 7 by following the "conversion curve of the image area ratio to the opening amount of the ink fountain key" stored in advance. The feed rate of the ink fountain roller 3 is set in accordance with a predetermined reference ink feed rate. The opening amounts of the ink fountain keys 4 and the feed rate of the ink fountain roller 3 (ink feed rate) are set in units of printing units 9-1 to 9-4. More specifically, the "conversion curve of the image area ratio to the opening amount of the ink fountain key" and the reference ink feed rate are determined in units of ink colors.

[0006] Conventionally, since the "conversion curve of the image area ratio to the opening amount of the ink fountain key" and the reference ink feed rate are uniquely determined by the printing machine manufacturer, differences in standard density among the printing companies and differences depending on the environment are not considered. For this reason, the operator of each printing company actually checks the color of the printed printing product after the opening amounts of the respective ink fountain keys 4 and the feed rate of the ink fountain roller 3 are set by using the standard characteristics in units of printing units 9-1 to 9-4.

[0007] In accordance with the result of color checking, the operator finely adjusts the opening amounts of the ink fountain keys 4 separately, or the feed rate of the ink

fountain roller 3, thereby dealing with the differences in standard density and the differences depending on the environment. This fine adjustment of the amount of ink to be supplied requires a very advanced technique and can be performed only by a skilled operator. The fine adjustment takes a very long period of time, leading to a delay in printing operation.

[0008] Also, conventionally, the "conversion curve of the image area ratio to the opening amount of the ink fountain key" and the reference ink feed rate must be stored in units of ink colors, and a very large memory capacity is accordingly necessary.

### Summary of the Invention

[0009] It is an object of the present invention to provide a method and apparatus for adjusting the ink supply amount for a multicolor printing press, which can perform color matching for actual printing and set and adjust the amount of ink to be supplied easily and within a short period of time.

[0010] It is another object of the present invention to provide a method and apparatus for adjusting the ink supply amount for a multicolor printing press, which do not require a very large memory capacity.

[0011] In order to achieve the above objects, according to the present invention, there is provided an ink supply amount adjusting method for a multicolor printing press which performs multicolor printing with a plurality of printing units provided to correspond to a plurality of ink colors, each of the printing units having an ink fountain for storing ink, an ink fountain roller to which the ink is supplied from the ink fountain, a plurality of ink fountain keys aligned in an axial direction of the ink fountain roller to adjust an amount of ink to be supplied from the ink fountain to the ink fountain roller, and an ink roller group for supplying the ink to a plate in an amount adjusted in accordance with a feed rate of the ink fountain roller, comprising the steps of

obtaining reference opening amounts of the ink fountain keys in units of ink colors in accordance with image area ratios of respective areas, corresponding to the ink fountain keys, of the plate by following a relationship between an image area ratio and opening amounts of the ink fountain keys, the relationship being preset to be common to the respective ink colors, and uniformly correcting the obtained reference opening amounts of the ink fountain keys in units of ink colors with correction values preset in units of ink colors, thereby obtaining set values of the opening amounts of the ink fountain keys in units of ink colors.

### Brief Description of the Drawings

[0012]

Fig. 1 is a block diagram of an ink supply amount adjusting apparatus for a printing press according to a first embodiment of the present invention;  
 Fig. 2 is a flow chart for explaining the operation of the ink supply amount adjusting apparatus of Fig. 1 before the start of printing;  
 Fig. 3 is a flow chart for explaining the operation of the ink supply amount adjusting apparatus of Fig. 1 at the start of printing;  
 Fig. 4 is a plan view of a testing plate used in the ink supply amount adjusting apparatus of Fig. 1;  
 Figs. 5A to 5C are graphs showing the relationship among the opening amount of the ink fountain key, the ink feed rate, and the reference printing density;  
 Fig. 6 is a block diagram of an ink supply amount adjusting apparatus for a printing press according to a second embodiment of the present invention;  
 Fig. 7 is a flow chart for explaining the operation of the ink supply amount adjusting apparatus of Fig. 6 before the start of printing;  
 Fig. 8 is a flow chart for explaining the operation of the ink supply amount adjusting apparatus of Fig. 6 at the start of printing;  
 Fig. 9 is a block diagram of an ink supply amount adjusting apparatus for a printing press according to a third embodiment of the present invention;  
 Fig. 10 is a flow chart for explaining the operation of the ink supply amount adjusting apparatus of Fig. 9 before the start of printing;  
 Fig. 11 is a flow chart for explaining the operation of the ink supply amount adjusting apparatus of Fig. 9 at the start of printing;  
 Fig. 12 is a block diagram of an ink supply amount adjusting apparatus for a printing press according to a fourth embodiment of the present invention;  
 Fig. 13 is a flow chart for explaining the operation of the ink supply amount adjusting apparatus of Fig. 12 before the start of printing;  
 Fig. 14 is a flow chart for explaining the operation of the ink supply amount adjusting apparatus of Fig. 12 at the start of printing;  
 Fig. 15 is a graph showing the "conversion curve of the image area ratio to the opening amount of the ink fountain key" of each ink color;  
 Fig. 16 is a graph showing the density obtained when the opening amount of the ink fountain key of an ink color is obtained from a corresponding conversion curve of cyan or magenta;  
 Fig. 17 is a view schematically showing an ink supply unit for a printing unit of each ink color in a rotary printing press;  
 Fig. 18 is a side view schematically showing a four-color rotary printing press; and  
 Figs. 19A, 19B, and 19C are function block dia-

grams of the CPUs respectively shown in Figs. 1, 9, and 12.

### Description of the Preferred Embodiments

[0013] The present invention will be described in detail with reference to the accompanying drawings. In the following description, Figs. 17 and 18 are also referred to.

#### [First Embodiment]

[0014] Referring to Fig. 1, the ink supply amount adjusting apparatus is comprised of a CPU (Central Processing Unit) 10, a ROM (Read Only Memory) 11, a RAM (Random Access Memory) 12, a switch group 13, a display 14, a drive 15 for a floppy disk or magnetic card, a printer 16, a densitometer 17, a measurement unit 18 for measuring the plate image area ratio of a testing plate, A/D (Analog-to-Digital) converters 19 and 20, input/output (I/O) interfaces 21 to 23, a reference density memory 24, a conversion curve memory 25, an ink feed rate memory 26, a correction amount memory 27, an ink fountain key drive unit 28, and an ink fountain roller drive unit 29.

[0015] The CPU 10 obtains various kinds of input information supplied through the input/output interfaces 21 to 23 and performs various processing operations in accordance with programs stored in the ROM 11 while accessing the RAM 12.

[0016] The standard densities in units of respective ink colors unique to the printing company (in units of printing units) are stored in the reference density memory 24 if necessary. Usually, when the printing press is shipped from the manufacturer, standard densities in units of ink colors are stored in the memory 24. The "conversion curve of the image area ratio to the opening amount of the ink fountain key" serving as the reference common to the ink colors is stored in the conversion curve memory 25. When the printing press is shipped from the manufacturer, the one and only standard characteristic common to the ink colors is stored in the memory 25.

[0017] The ink feed rates in units of ink colors are stored in the ink feed rate memory 26. When the printing press is shipped from the manufacturer, the reference ink feed rates in units of ink colors are stored in the memory 26 as the standard values. The correction amounts (increments/decrements) of the opening amounts of the ink fountain keys in units of ink colors are stored in the correction amount memory 27 as the uniform values for the respective ink fountain keys 4. More specifically, correction amounts common to all the ink fountain keys 4 (Fig. 17) are set as the correction amounts of the opening amounts of the ink fountain keys in units of ink colors. When the printing press is shipped from the manufacturer, the correction amounts of the opening amounts of the ink fountain keys are set to 0 for each ink color.

[0018] The ink fountain key drive unit 28 is separately provided to correspond to each ink fountain key 4 of each of the printing units 9-1 to 9-4. More specifically, in each of the printing units 9-1 to 9-4, n (n is a positive integer of 2 or more) ink fountain key drive units 28 are provided to correspond to the n ink fountain keys 4. In this case, the opening amounts of the n ink fountain keys 4 with respect to the ink fountain roller 3 are separately adjusted by the n ink fountain key drive units 28 having the same arrangement.

[0019] The ink fountain key drive unit 28 has an input/output interface 28A, a D/A converter 28B, a fountain key motor driver 28C, a fountain key motor 28D, a potentiometer 28E added to the fountain key motor 28D, and an A/D converter 28F.

[0020] The ink fountain roller drive unit 29 is separately provided to correspond to each ink fountain roller 3 of each of the printing units 9-1 to 9-4. More specifically, in the four-color printing press, four ink fountain roller drive units 29 are provided to correspond to the four printing units 9-1 to 9-4. In this case, the feed rates of the ink fountain rollers 3 of the respective printing units 9-1 to 9-4 are separately adjusted by the four ink fountain roller drive units 29 having the same arrangement.

[0021] The ink fountain roller drive unit 29 has an input/output interface 29A, a D/A converter 29B, a fountain roller driving motor driver 29C, a fountain roller driving motor 29D, a rotary encoder 29E added to the fountain roller driving motor 29D, an F/V converter 29F, and an A/D converter 29G. [How to Adjust Correction Amount of Opening Amount of Ink Fountain Key and Ink Feed Rate in Adjustment Before Actual Printing (Fig. 2)]

[0022] Prior to the start of printing, the correction amounts of the opening amounts of the ink fountain keys in units of ink colors stored in the correction amount memory 27 and the ink feed rates in units of ink colors stored in the ink feed rate memory 26 are adjusted. In this adjustment, testing plates 7A having the same image as shown in Fig. 4 are used in units of ink colors. A color patch portion 7A1 and ink supply amount adjusting image portion 7A2 are formed on each testing plate 7A.

[0023] The color patch portion 7A1 is a known image portion used for measuring printing quality, and is constituted by a plurality of patches (not shown) which are printed in the respective areas corresponding to the ink fountain keys 4 to be continuous in the direction of array of the ink fountain keys 4. The ink supply amount adjusting image portion 7A2 has a right-angled triangular shape, and the image area ratios within the respective areas corresponding to the ink fountain keys 4 gradually change in the direction along which the ink fountain keys 4 are aligned.

[0024] To adjust the correction amounts of the opening amounts of the ink fountain keys 4 and the ink feed rate, the operator measures the image area ratios of the testing plate 7A with the measurement unit 18 and supplies them to the CPU 10 (step S101). More specifically, the operator measures the image area ratios, corre-

sponding to the ink fountain keys 4, of the respective areas of the testing plate 7A, and supplies them to the CPU 10 through the A/D converter 20 and input/output interface 22.

[0025] The CPU 10 calculates the reference opening amounts of the ink fountain keys 4 of the respective ink colors in accordance with the image area ratios, corresponding to the ink fountain keys 4, of the respective areas of the testing plate 7A by following the "conversion curve (standard characteristics) of the image area ratio to the opening amount of the ink fountain key" common to the ink colors (step S102) and stored in the conversion curve memory 25 in advance. At this time, the reference opening amounts of the ink fountain keys 4 of the respective ink colors are common to the respective ink colors.

[0026] The ink feed rates in units of ink colors are read out from the ink feed rate memory 26 (step S103), and the read-out ink feed rates of the respective ink colors are set in the ink fountain rollers 3 of the printing units 9-1 to 9-4 through the ink fountain roller drive unit 29. The reference opening amounts of the ink fountain keys 4 of the respective ink colors obtained in step S102 are also set through the ink fountain key drive unit 28 (step S104).

[0027] With the four testing plates 7A being set on the plate cylinders 8 of the respective ink colors, the operator performs printing to acquire a printing sample (step S105). The density of each ink color of the acquired printing sample is measured with the densitometer 17 (step S106), and is supplied to the CPU 10 through the A/D converter 19 and input/output interface 21. On the basis of data supplied from the densitometer 17, the CPU 10 checks whether the density (measured density) of each area, corresponding to the ink fountain key 4, of each ink color of the printing sample coincides with the corresponding reference density (the reference density unique to the printing company) of each ink color stored in the reference density memory 24 in advance (step S107).

[0028] If the measured density and the reference density do not coincide with each other, i.e., if the difference between the measured density and reference density is not zero or does not fall within a predetermined range, the CPU 10 determines that the density must be adjusted. For the sake of descriptive convenience, assume that the measured density and the reference density do not coincide with each other in all areas of the respective ink colors.

[0029] When the density has to be adjusted, the operator adjusts the correction amounts of the opening amounts of the ink fountain keys in units of ink colors stored in the correction amount memory 27 and the ink feed rates of the respective ink colors stored in the ink feed rate memory 26 (step S108). More specifically, the operator increases or decreases the current correction amounts of the opening amounts of the ink fountain keys of the respective ink colors and the current ink feed rates

in units of ink colors while monitoring them displayed on the display 14. The adjusted correction amounts of the opening amounts of the ink fountain keys and the adjusted ink feed rates, of the respective ink colors are overwritten in the correction amount memory 27 and ink feed rate memory 26.

[0030] The CPU 10 reads out the adjusted correction amounts of the opening amounts of the ink fountain keys of the respective ink colors from the correction amount memory 27 (step S109). The CPU 10 then adds the read-out correction amounts of the opening amounts of the ink fountain keys of the respective ink colors to the reference opening amounts of the ink fountain keys 4 of the respective ink colors obtained in step S102, thereby correcting the opening amounts of the ink fountain keys 4 of the respective ink colors (step S110). More specifically, if the correction amounts are positive values, they are uniformly added to the opening amounts of the ink fountain keys 4; if they are negative values, they are uniformly subtracted from the opening amounts of the ink fountain keys 4.

[0031] The CPU 10 then reads out the adjusted ink feed rates of the respective ink colors from the ink feed rate memory 26 (step S111). The read-out ink feed rates of the respective ink colors, and the opening amounts of the ink fountain keys 4 of the respective ink colors corrected in step S110, are set in the CPU 10 through the ink fountain roller drive unit 29 and ink fountain key drive unit 28 (step S112).

[0032] In each ink color, if the measured density obtained in step S107 is a constant value A, as indicated by a characteristic curve I shown in Fig. 5A, regardless of the image area ratio, this characteristic curve is changed by adjusting the ink feed rate in step S112. For example, when the ink feed rate is increased, the density increases, as indicated by a characteristic curve II. The density does not increase sharply at a portion with a low image area ratio, but increases gradually as the image area ratio increases, and stays at a substantially constant value when the image area ratio reaches a certain value.

[0033] In each ink color, if the measured density obtained in step S107 is a constant value A, as indicated by a characteristic curve I shown in Fig. 5B, regardless of the image area ratio, this characteristic curve is changed by adjusting the opening amounts of the respective ink fountain keys 4 in step S112. For example, when the opening amounts of the ink fountain keys 4 are uniformly increased, the density increases, as indicated by a characteristic curve III. The density increases largely at a portion with a low image area ratio, but decreases gradually as the image area ratio increases, and stays at substantially a constant value when the image area ratio reaches a certain value.

[0034] In step S112, since both the ink feed rates and the opening amounts of the ink fountain keys are adjusted, the characteristic curves II and III are combined to provide a characteristic curve IV, as shown in Fig. 5C.

The printing density of each ink color can be adjusted to a desired density (reference density) B by translation without changing the "conversion curve of the image area ratio to the opening amount of the ink fountain key" common to the respective ink colors and stored in the conversion curve memory 25.

[0035] Fig. 15 shows the conventional "conversion curve of the image area ratio to the opening amount of ink fountain key" of each of cyan, magenta, yellow, and black which are the respective ink colors. When the opening amounts of the ink fountain keys of cyan or magenta are obtained from the corresponding conversion curve and printing is performed with the obtained opening amount, the density as shown in Fig. 16 is obtained. As is apparent from Fig. 16, the density of black has a density distribution substantially opposite to that obtained when the feed rate of the ink fountain roller is increased, and the density of yellow has a density distribution substantially opposite to that obtained when the opening amounts of the ink fountain keys are uniformly increased.

[0036] These density distributions can be set almost uniform by uniformly increasing/decreasing the feed rate of the ink fountain roller or the opening amounts of the ink fountain keys. Hence, the density distributions of the respective ink colors can be set uniform. The densities of the respective ink colors are different from the corresponding reference densities. As described above, however, the densities of portions with the respective image area ratios can be changed substantially uniformly by uniformly increasing/decreasing the feed rate of the ink fountain roller or the opening amounts of the ink fountain keys. By this adjustment, the densities of the respective ink colors can be set to match the reference densities of the corresponding ink colors of each printing company.

[0037] As a result, when the feed rate of the ink fountain key roller and the opening amounts of the ink fountain keys are uniformly increased or decreased by using the "conversion curve of the image area ratio to the opening amount of the ink fountain key" common to the ink colors, the amount of ink to be supplied, which matches the reference density of each ink color of each printing company or the printing condition, can be obtained. In a subsequent printing operation, the appropriate amount of ink to be supplied can be obtained easily by using the increment(s)/decrement(s) of the feed rate of the ink fountain roller and the opening amounts of the ink fountain keys.

[0038] After the ink feed rate and the opening amounts of the ink fountain keys are set in step S112, the operator performs printing again with the testing plate 7A being set on the plate cylinder 8 of each ink color, and acquires a printing sample (step S113). The operator then measures the density of each ink color of the acquired printing sample (step S114). The CPU 10 checks whether the measured density of each area, corresponding to the ink fountain key 4, of the correspond-

ing ink color of the acquired printing sample coincides with the reference density in the same manner as in the previous step S107 (step S115).

[0039] The CPU 10 repeats the steps S108 to S115 until the measured densities of all areas of the respective ink colors coincide with the reference densities. When the measured densities of all areas of the respective ink colors coincide with the reference densities, the CPU 10 ends adjustment of the correction amounts of the opening amounts of the ink fountain keys and the ink feed rates performed before the start of printing.

[How to Set Ink Supply Amount at Start of Actual Printing (Fig. 3)]

[0040] Prior to the start of printing with the plate 7 of each ink color being mounted, the operator separately measures the image area ratio of the plate 7 of each ink color with the plate image area ratio measurement unit 18, and supplies the obtained ratio to the CPU 10 (step S201). More specifically, the operator measures the image area ratios, corresponding to the ink fountain keys 4, of the respective areas of the plates 7 of the respective ink colors, and supplies the measured image area ratios to the CPU 10 through the A/D converter 20 and input/output interface 22.

[0041] The CPU 10 obtains the reference opening amounts of the ink fountain keys 4 of the respective ink colors in accordance with the image area ratios of the respective areas, corresponding to the ink fountain keys 4, of the plate 7 of the respective ink colors by following the "conversion curve of the image area ratio to the opening amount of the ink fountain key" common to the ink colors (step S202) and stored in the conversion curve memory 25 in advance. The operator then reads out the correction amounts of the opening amounts of the ink fountain keys of the respective ink colors from the correction amount memory 27 (step S203). The CPU 10 then adds the read-out correction amounts of the opening amounts of the ink fountain keys of the respective ink colors to the reference opening amounts of the ink fountain keys 4 of the respective ink colors obtained in step S202, thereby obtaining preset values of the opening amounts of the ink fountain keys 4 for the respective ink colors (step S204). More specifically, if the correction amounts are positive amounts, they are uniformly added to the opening amounts of the ink fountain keys 4; if they are negative values, they are uniformly subtracted from the opening amounts of the ink fountain keys 4.

[0042] The CPU 10 then reads out the ink feed rates of the respective ink colors from the ink feed rate memory 26 (step S205). The read-out ink feed rates of the respective ink colors, and the opening amounts of the ink fountain keys 4 of the respective ink colors obtained in step S204, are set in the CPU 10 through the ink fountain roller drive unit 29 and ink fountain key drive unit 28 (step S206). Printing is then started (step S207).

[0043] In this case, the ink feed rates of the respective ink colors in the ink feed rate memory 26 and the correction amounts of the opening amounts of the ink fountain keys of the respective ink colors in the correction amount memory 27 are adjusted such that the reference densities of the respective ink colors unique to the printing company are obtained by repeating steps S108 to S115 before the start of printing regardless of the image area ratios. Therefore, appropriate ink supply amounts can be obtained from the beginning.

[0044] More specifically, conventionally, the opening amounts of the ink fountain keys 4 and the ink feed rates, of the respective ink colors are set in accordance with the reference densities unique to the printing company to be employed and the printing environmental conditions, and after that the operator adjusts the opening amounts of the ink fountain keys and the ink feed rates of the respective ink colors without regularity while repeating printing test of the printing products with the plates 7, such that appropriate amounts of ink are supplied. According to this embodiment, such ink supply amount adjustment with the plates 7 being mounted is not necessary. Appropriate amounts of ink can be obtained immediately after the plates 7 are mounted.

[0045] According to this embodiment, since the correction amounts of the opening amounts of the ink fountain keys of the respective ink colors are uniform, the correction amounts and ink feed rates can be adjusted before the start of printing easily within a short period of time when compared to a method of setting separate correction amounts in units of ink fountain keys. The basic "conversion curve of the image area ratio to the opening amount of the ink fountain key" determined by the printing machine manufacturer and common to the ink colors need not be changed, and the adjusting operation can be simplified.

[0046] According to this embodiment, since only the "conversion curve of the image area ratio to the opening amount of the ink fountain key" common to the ink colors need be stored in the conversion curve memory 25, the memory capacity of the conversion curve memory 25 can be greatly reduced. More specifically, conventionally, since the "conversion curve of the image area ratio to the opening amount of the ink fountain key" is stored in units of ink colors, a large memory capacity is needed. According to the present invention, the one and only "conversion curve of the image area ratio to the opening amount of the ink fountain key" need be stored, and a large memory capacity is not needed.

[0047] According to this embodiment, both the correction amounts of the opening amounts of the ink fountain keys and the ink feed rates, of the respective ink colors are adjusted. In some cases, only either the correction amounts of the opening amounts of the ink fountain keys or the ink feed rates, of the respective ink colors need be adjusted. For example, in Fig. 5B, within an image area ratio range where the characteristic curve III of the density translates, a desired density B can be obtained

only by adjusting the correction amounts of the opening amounts of the ink fountain keys of the respective ink colors. In Fig. 5A, within an image area ratio range where the characteristic curve II of the density translates, a desired density B can be obtained only by adjusting the ink feed rates of the respective ink colors.

[0048] When the density obtained by printing with the conditions set by the printing machine manufacturer exhibits a characteristic curve III as shown in Fig. 5B, the desired density B can be obtained only by adjusting the ink feed rates. When the density obtained by printing exhibits a characteristic curve II shown in Fig. 5A, the desired density B can be obtained only by adjusting the correction amounts of the opening amounts of the ink fountain keys.

[Second Embodiment]

[0049] Referring to Fig. 6, the same reference numerals as in Fig. 1 denote the same or equivalent constituent elements, and a detailed description thereof will be omitted.

[0050] The ink supply amount adjusting apparatus according to this embodiment has, in addition to the arrangement shown in Fig. 1, a coefficient memory 30 for storing the coefficients of ink feed rates in units of ink colors. The coefficients of the ink feed rates in units of ink colors (in units of printing units) are set to "1" when the printing machine is shipped from the manufacturer. The one and only reference ink feed rate common to the ink colors is stored in an ink feed rate memory 26 when the printing machine is shipped from the manufacturer. Unlike the first embodiment, the reference ink feed rate common to the ink colors will not be overwritten.

[How to Adjust Correction Amount of Opening Amount of Ink Fountain Key and Coefficient of Ink Feed Rate in Adjustment Before Actual Printing (Fig. 7)]

[0051] Prior to the start of printing, the correction amounts of the opening amounts of the ink fountain keys in units of ink colors stored in a correction amount memory 27 and the coefficients of the ink feed rates in units of ink colors stored in a coefficient memory 30 are adjusted. In this adjustment as well, testing plates 7A identical to that shown in Fig. 4 are used.

[0052] The processes of steps S301 to S307 and S314 to S316 in Fig. 7 are the same as those of steps S101 to S107 and S113 to S115 in Fig. 2, and a description thereof will accordingly be omitted.

[0053] When it is determined in step S307 that the density need be adjusted, the operator adjusts the correction amounts of the opening amounts of the ink fountain keys of the respective ink colors stored in the correction amount memory 27 and the coefficients of the ink feed rates of the respective ink colors stored in the coefficient memory 30 (step S308). More specifically, the operator increases or decreases the current correc-

tion amounts of the opening amounts of the ink fountain keys and the current coefficients of the ink feed rates, of the respective ink colors while monitoring them displayed on a display 14. The adjusted correction amounts of the opening amounts of the ink fountain keys and the adjusted coefficients of the ink feed rates, of the respective ink colors are overwritten in the correction amount memory 27 and coefficient memory 30, respectively.

[0054] The CPU 10 reads out the adjusted correction amounts of the opening amounts of the ink fountain keys of the respective ink colors from the correction amount memory 27 (step S309). The CPU 10 then adds the read-out correction amounts (increments/decrements) of the opening amounts of the ink fountain keys of the respective ink colors to the reference opening amounts of the ink fountain keys 4 of the respective ink colors obtained in step S302, thereby correcting the opening amounts of ink fountain keys 4 of the respective ink colors (step S310). More specifically, if the correction amounts are positive values, they are uniformly added to the opening amounts of the ink fountain keys 4; if they are negative values, they are uniformly subtracted from the opening amounts of the ink fountain keys 4.

[0055] The CPU 10 then reads out the adjusted coefficients of the ink feed rates of the respective ink colors from the coefficient memory 30 (step S311). The CPU 10 multiplies the reference ink feed rate, read by the step S303 and common to the ink colors, by the read-out coefficients of the ink feed rates of the respective ink colors, thereby correcting the ink feed rates of the respective ink colors (step S312). Subsequently, the CPU 10 sets the opening amounts of the ink fountain keys 4 of the respective ink colors obtained in step S310 and the ink feed rates of the respective ink colors obtained in step S312 through an ink fountain key drive unit 28 and ink fountain roller drive unit 29 (step S313). When the setting operation is ended, the flow advances to step S315.

[How to Set Ink Supply Amount at Start of Actual Printing (Fig. 8)]

[0056] Processes of steps S401 to S404 in Fig. 8 are the same as those of steps S201 to S204 in Fig. 3, and a description thereof will accordingly be omitted.

[0057] The CPU 10 reads out the reference ink feed rate common to the ink colors from the ink feed rate memory 26 in step S405, and reads the coefficients of the ink feed rates of the respective ink colors from the coefficient memory 30 (step S406). The CPU 10 then multiplies the reference ink feed rate, read in step S405 and common to the ink colors, by the read-out coefficients of the ink feed rates of the respective ink colors, thereby obtaining preset values of the ink feed rates of the respective ink colors (step S407).

[0058] The CPU 10 sets the opening amounts of the ink fountain keys 4 of the respective ink colors obtained



in step S404, and the ink feed rates of the respective ink colors obtained in step S407 through the ink fountain key drive unit 28 and ink fountain roller drive unit 29 (step S408). Printing is then started (step S409).

**[0059]** In this embodiment, the ink feed rates of the respective ink colors are corrected by multiplying them by the coefficients. Alternatively, if correction values are obtained and added to the reference ink feed rate, in the same manner as that performed when adjusting the opening amounts of the ink fountain keys, the same effect can be obtained.

#### [Third Embodiment]

**[0060]** Referring to Fig. 9, the same reference numerals as in Fig. 1 denote the same or equivalent constituent elements, and a detailed description thereof will be omitted.

**[0061]** The ink supply amount adjusting apparatus according to this embodiment has, in addition to the arrangement shown in Fig. 1, a zero position memory 31 for storing the zero positions (origin positions) of the opening amounts of the ink fountain keys in units of ink colors.

[How to Adjust Correction Amount of Opening Amount of Ink Fountain Key and Ink Feed Rate in Adjustment Before Actual Printing (Fig. 10)]

**[0062]** Prior to the start of printing, the correction amounts of the opening amounts of the ink fountain keys in units of ink colors stored in a correction amount memory 27 and the ink feed rates in units of ink colors stored in an ink feed rate memory 26 are adjusted. In this adjustment as well, testing plates 7A identical to that shown in Fig. 4 are used. The processes of steps S501 to S515 in Fig. 10 are the same as those of steps S101 to S115 in Fig. 2, and a description thereof will be omitted.

[How to Set Ink Supply Amount at Start of Actual Printing (Fig. 11)]

**[0063]** The operator measures the image area ratio of the testing plate 7A with a measurement unit 18 and supplies it to a CPU 10 (step S601). The CPU 10 reads out the zero positions of the opening amounts of the ink fountain keys of the respective ink colors stored in the zero position memory 31 (step S602), and the correction amounts of the opening amounts of the ink fountain keys of the respective ink colors stored in the correction amount memory 27 (step S603). Subsequently, the CPU 10 adds the correction amounts (increments/decrements) of the opening amounts of the ink fountain keys of the respective ink colors to the readout zero positions of the opening amounts of the ink fountain keys of the respective ink colors, thereby correcting the zero positions of the opening amounts of the ink fountain keys of

the respective ink colors (step S604). More specifically, if the correction amounts are positive values, they are uniformly added to the zero positions of the opening amounts of the ink fountain keys; if they are negative values, they are uniformly subtracted from the zero positions of the opening amounts of the ink fountain keys.

**[0064]** The CPU 10 obtains the reference opening amounts of the ink fountain keys 4 of the respective ink colors in accordance with the image area ratios of the respective areas, corresponding to the ink fountain keys 4, of the plates 7 of the respective ink colors by following the "conversion curve of the image area ratio to the opening amount of the ink fountain key" common to the ink colors (step S605) and stored in a conversion curve memory 25 in advance. The operator then obtains the opening amounts of the ink fountain keys of the respective ink colors from the corrected zero positions of the opening amounts of the ink fountain keys of the respective ink colors obtained in step S604 and the reference opening amounts of the ink fountain keys of the respective ink colors obtained in step S605 (step S606).

**[0065]** The CPU 10 reads out the ink feed rates of the respective ink colors from the ink feed rate memory 26 (step S607). The CPU 10 then sets the read-out ink feed rates of the respective ink colors and the opening amounts of ink fountain keys 4 of the respective ink colors obtained in step S606 through an ink fountain roller drive unit 29 and ink fountain key drive unit 28 (step S608). After that, printing is started (step S609).

**[0066]** In this case, the opening amounts of the ink fountain keys 4 of the respective ink colors are set with reference to the corrected zero positions of the opening amounts of the ink fountain keys of the respective ink colors. More specifically, the opening amounts of the ink fountain keys 4 of the respective ink colors are set with reference to the zero positions that are adjusted such that the reference densities of the respective ink colors unique to the printing company can be obtained regardless of the image area ratio. Therefore, when the setting operation of the opening amounts is combined with the setting operation of the ink feed rates of the respective ink colors read from the ink feed rate memory 26, appropriate ink supply amounts can be obtained from the beginning.

#### [Fourth Embodiment]

**[0067]** Referring to Fig. 12, the same reference numerals as in Fig. 6 denote the same or equivalent constituent elements, and a detailed description thereof will be omitted.

**[0068]** The ink supply amount adjusting mechanism according to this embodiment has, in addition to the arrangement shown in Fig. 6, a memory 31 for storing the zero positions (origin positions) of the opening amounts of the ink fountain keys in units of ink colors. [How to Adjust Correction Amount of Opening Amount of Ink Fountain Key and Coefficient of Ink Feed Rate in Ad-

justment Before Actual Printing (Fig. 13)]

[0069] Prior to the start of printing, the correction amounts of the opening amounts of the ink fountain keys in units of ink colors stored in a correction amount memory 27 and the coefficients of the ink feed rates in units of ink colors stored in a memory 30 are adjusted. In this adjustment as well, testing plates 7A identical to that shown in Fig. 4 are used. The processes of steps S701 to S716 in Fig. 13 are the same as those of steps S301 to S316 in Fig. 7, and a description thereof will be omitted.

[How to Set Ink Supply Amount at Start of Actual Printing (Fig. 14)]

[0070] The operator measures the image area ratio of the testing plate 7A with a measurement unit 18 and supplies it to a CPU 10 (step S801). The CPU 10 reads out the zero positions of the opening amounts of the ink fountain keys of the respective ink colors stored in the zero position memory 31 (step S802), and the correction amounts of the opening amounts of the ink fountain keys of the respective ink colors stored in the correction amount memory 27 (step S803). Subsequently, the CPU 10 adds the correction amounts (increments/decrements) of the opening amounts of the ink fountain keys of the respective ink colors to the read-out zero positions of the opening amounts of the ink fountain keys of the respective ink colors, thereby correcting the zero positions of the opening amounts of the ink fountain keys of the respective ink colors (step S804). More specifically, if the correction amounts are positive values, they are uniformly added to the zero positions of the opening amounts of the ink fountain keys; if they are negative values, they are uniformly subtracted from the zero positions of the opening amounts of the ink fountain keys.

[0071] The CPU 10 obtains the reference opening amounts of the ink fountain keys 4 of the respective ink colors in accordance with the image area ratios of the respective areas, corresponding to ink fountain keys, of the plate 7 of the respective ink colors 4 by following the "conversion curve of the image area ratio to the opening amount of the ink fountain key" common to the ink colors (step S805) and stored in a conversion curve memory 25 in advance. The CPU 10 then obtains the opening amounts of the ink fountain keys of the respective ink colors from the corrected zero positions of the opening amounts of the ink fountain keys of the respective ink colors obtained in step S804 and the reference opening amounts of the ink fountain keys of the respective ink colors obtained in step S805 (step S806).

[0072] The CPU 10 reads out the reference ink feed rate common to the ink colors from an ink feed rate memory 26 (step S807), and the coefficients of the ink feed rates of the respective ink colors from the coefficient memory 30 (step S808). The CPU 10 then multiplies the reference ink feed rate common to the ink colors and read in step S807 by the read-out coefficients

of the ink feed rates of the respective ink colors, thereby obtaining preset values of the ink feed rates of the respective ink colors (step S809).

[0073] The CPU 10 sets the opening amounts of the ink fountain keys 4 of the respective ink colors obtained in step S806 and the ink feed rates of the respective ink colors obtained in step S809 through an ink fountain key drive unit 28 and ink fountain roller drive unit 29. After that, printing is started (step S811).

[0074] In this case, the opening amounts of the ink fountain keys 4 of the respective ink colors are set with reference to the corrected zero positions of the opening amounts of the ink fountain keys of the respective ink colors. More specifically, the opening amounts of the ink fountain keys 4 of the respective ink colors are set with reference to the zero positions that are adjusted such that the reference densities of the respective ink colors unique to the printing company can be obtained regardless of the image area ratio. Therefore, when the setting operation of the opening amounts is combined with the setting operation of the ink feed rates of the respective ink colors obtained in step S809, appropriate ink supply amounts can be obtained from the beginning.

[0075] In this embodiment, the ink feed rates of the respective ink colors are corrected by multiplying them by the coefficients. Alternatively, if correction values are obtained and added to the reference ink feed rates, in the same manner as that performed when adjusting the opening amounts of the ink fountain keys, the same effect can be obtained.

[0076] Figs. 19A, 19B, and 19C show the relationships between the function blocks of the CPUs 10 of Figs. 1, 9, and 12 and their processing steps. In the CPU 10 of Fig. 1 shown in Fig. 19A, a first reference opening amount calculating portion 101 performs the process of step S102 of Fig. 2, and an opening amount correction value calculating portion 102 performs the processes of steps S108 to S115 of Fig. 2. A second reference opening amount calculating portion 103 performs the process of step S202 of Fig. 3, and an opening amount preset value calculating portion 104 performs the process of step S206 of Fig. 3. The same applies to the CPU 10 shown in Fig. 6.

[0077] In the CPU 10 of Fig. 9 shown in Fig. 19B, a first reference opening amount calculating portion 201 performs the process of step S502 of Fig. 10, and an opening amount correction value calculating portion 202 performs the processes of steps S503 to S515 of Fig. 10. An origin position correcting portion 203 performs the process of step S604 of Fig. 11, and an opening amount preset value calculating portion 204 performs the process of step S606 of Fig. 11.

[0078] In the CPU 10 of Fig. 12 shown in Fig. 19C, an overwriting portion 301 performs the processes of steps S708 to S716 of Fig. 13, a feed rate correction value setting portion 302 performs the process of step S808 of Fig. 14, and a feed rate preset value calculating portion 303 performs the process of step S809 of Fig. 14.

A CPU 10 of Fig. 12 can also have at least one functional block of the CPUs 10 of Figs. 1 and 9.

[0079] As has been described above, according to the present invention, color matching in actual printing can be performed easily within a short period of time. In particular, when at least one of the correction amounts/origin positions of the opening amounts of the ink fountain keys of the respective ink colors and the correction values of the ink feed rates of the respective ink colors is adjusted such that the reference densities of the respective ink colors unique to the printing company can be obtained regardless of the image area ratio before the start of printing, a higher effect can be obtained. As the relationship between the image area ratio and the opening amounts of the ink fountain keys, it suffices if only one reference value is set to be common to the respective ink colors. Therefore, no large memory capacity is needed, and the image capacity can be reduced greatly.

[0080] According to the present invention, the correction amounts of the opening amounts of the ink fountain keys and the correction amounts of the ink feed rates, of the ink colors can be overwritten. Therefore, the amount of ink to be supplied, which varies depending on the printing companies and the differences in the environment, can be adjusted easily within a short period of time by adjusting the correction values (increments/decrements) of the opening amounts of the ink fountain keys and the correction amounts of the ink feed rates, of the ink colors before the start of printing.

## Claims

1. An ink supply amount adjusting method for a multi-color printing press which performs multicolor printing with a plurality of printing units (9-1 - 9-4) provided to correspond to a plurality of ink colors, each of said printing units having an ink fountain (1) for storing ink (2), an ink fountain roller (3) to which said ink is supplied from said ink fountain, a plurality of ink fountain keys (4) aligned in an axial direction of said ink fountain roller to adjust an amount of ink to be supplied from said ink fountain to said ink fountain roller, and an ink roller group (6) for supplying said ink to a plate (7) in an amount adjusted in accordance with a feed rate of said ink fountain roller, characterized by comprising the steps of

obtaining reference opening amounts of said ink fountain keys in units of ink colors in accordance with image area ratios of respective areas, corresponding to said ink fountain keys, of said plate by following a relationship between an image area ratio and opening amounts of said ink fountain keys, the relationship being preset to be common to the respective ink colors, and  
uniformly correcting the obtained reference

opening amounts of said ink fountain keys in units of ink colors with correction values preset in units of ink colors, thereby obtaining set values of the opening amounts of said ink fountain keys in units of ink colors.

2. An ink supply amount adjusting method for a multi-color printing press which performs multicolor printing with a plurality of printing units (9-1 - 9-4) provided to correspond to a plurality of ink colors, each of said printing units having an ink fountain (1) for storing ink (2), an ink fountain roller (3) to which said ink is supplied from said ink fountain, a plurality of ink fountain keys (4) aligned in an axial direction of said ink fountain roller to adjust an amount of ink to be supplied from said ink fountain to said ink fountain roller, and an ink roller group (6) for supplying said ink to a plate (7) in an amount adjusted in accordance with a feed rate of said ink fountain roller, characterized by comprising the steps of

uniformly presetting correction values of opening amounts of said ink fountain keys in units of ink colors,

correcting origin positions of the opening amounts of said ink fountain keys in units of ink colors by using the preset correction values, and

setting the opening amounts of said ink fountain keys of the respective ink colors in accordance with image area ratios of respective areas, corresponding to said ink fountain keys, of said plate of the respective ink colors by following a relationship, preset to be common to the ink colors, between an image area ratio and the opening amounts of said ink fountain keys.

3. A method according to claim 1 or 2, further comprising the step of overwriting the correction values of the opening amounts of said ink fountain keys in units of ink colors.
4. A method according to claim 3, wherein the overwriting step comprises the steps of

obtaining reference opening amounts of said ink fountain keys of the respective ink colors, prior to start of actual printing, by following the relationship, preset to be common to the respective ink colors, between the image area ratio and the opening amounts of said ink fountain keys, and

obtaining correction values of the obtained reference opening amounts of said ink fountain keys of the respective ink colors on the basis of measured densities in units of ink colors of a printing sample printed by using testing plates of the respective ink colors having the same im-

age area ratio.

5. An ink supply amount adjusting method for a multi-color printing press which performs multicolor printing with a plurality of printing units (9-1 - 9-4) provided to correspond to a plurality of ink colors, each of said printing units having an ink fountain (1) for storing ink (2), an ink fountain roller (3) to which said ink is supplied from said ink fountain, a plurality of ink fountain keys (4) aligned in an axial direction of said ink fountain roller to adjust an amount of ink to be supplied from said ink fountain to said ink fountain roller, and an ink roller group (6) for supplying said ink to a plate (7) in an amount adjusted in accordance with a feed rate of said ink fountain roller, characterized by comprising the steps of
  - presetting correction values of feed rates of said ink fountain rollers in units of ink colors, and
  - correcting a reference feed rate of said ink fountain roller preset to be common to the ink colors by using the preset correction values, thereby setting the feed rates of said ink fountain rollers of the respective ink colors.
6. A method according to claim 5, further comprising the step of overwriting the correction values of the feed rates of said ink fountain rollers in units of ink colors.
7. A method according to claim 5 or 6, further comprising the steps of
  - obtaining reference opening amounts of said ink fountain keys of the respective ink colors in accordance with image area ratios of respective areas, corresponding to said ink fountain keys, of said plate of the respective ink colors by following a relationship, preset to be common to the respective ink colors, between an image area ratio and the opening amounts of said ink fountain keys, and
  - uniformly correcting the obtained reference opening amounts of said ink fountain keys of the respective ink colors with the correction values preset in units of ink colors, thereby obtaining set values of the opening amounts of said ink fountain keys of the respective ink colors.
8. A method according to any one of claims 5 to 7, further comprising the steps of
  - uniformly presetting the correction values of the opening amounts of said ink fountain keys in units of ink colors,
  - correcting origin positions of the opening amounts of said ink fountain keys of the respec-

tive ink colors by using the preset correction values, and  
obtaining the opening amounts of said ink fountain keys of the respective ink colors in accordance with image area ratios of respective areas,

corresponding to said ink fountain keys, of said plate of the respective ink colors by following a relationship, preset in advance to be common to the respective ink colors, between an image area ratio and the opening amounts of said ink fountain keys.

9. An ink supply amount adjusting apparatus for a multicolor printing press which performs multicolor printing with a plurality of printing units (9-1 - 9-4) provided to correspond to a plurality of ink colors, each of said printing units having an ink fountain (1) for storing ink (2), an ink fountain roller (3) to which said ink is supplied from said ink fountain, a plurality of ink fountain keys (4) aligned in an axial direction of said ink fountain roller to adjust an amount of ink to be supplied from said ink fountain to said ink fountain roller, and an ink roller group (6) for supplying said ink to a plate (7) in an amount adjusted in accordance with a feed rate of said ink fountain roller, characterized by comprising
  - first calculating means (103) for obtaining reference opening amounts of said ink fountain keys in units of ink colors in accordance with image area ratios of respective areas, corresponding to said ink fountain keys, of said plate by following a relationship between an image area ratio and opening amounts of said ink fountain keys, the relationship being preset to be common to the respective ink colors, and
  - second calculating means (104) for uniformly correcting the reference opening amounts of said ink fountain keys of the respective ink colors output from said first calculating means with correction amounts preset in units of ink colors, thereby obtaining set values of the opening amounts of said ink fountain keys of the respective ink colors.
10. An apparatus according to claim 9, further comprising overwriting means for overwriting the correction values of the opening amounts of said ink fountain keys in units of ink colors.
11. An apparatus according to claim 10, wherein said overwriting means comprises

third calculating means (101) for obtaining the reference opening amounts of said ink fountain keys of the respective ink colors, prior to actual start of actual printing, by following the relation-

- ship, preset to be common to the respective ink colors, between the image area ratio and the opening amounts of said ink fountain keys, and presetting means (102) for presetting the correction values of the reference opening amounts of said ink fountain keys of the respective ink colors output from said third calculating means on the basis of measured densities in units of ink colors of a printing sample printed by using testing plates of the respective ink colors having the same image area ratio.
12. An ink supply amount adjusting apparatus for a multicolor printing press which performs multicolor printing with a plurality of printing units (9-1 - 9-4) provided to correspond to a plurality of ink colors, each of said printing units having an ink fountain (1) for storing ink (2), an ink fountain roller (3) to which said ink is supplied from said ink fountain, a plurality of ink fountain keys (4) aligned in an axial direction of said ink fountain roller to adjust an amount of ink to be supplied from said ink fountain to said ink fountain roller, and an ink roller group (6) for supplying said ink to a plate (7) in an amount adjusted in accordance with a feed rate of said ink fountain roller, characterized by comprising
- correction means (203) for correcting origin positions of the opening amounts of said ink fountain keys of the respective ink colors by using the correction values of the opening amounts of said ink fountain keys preset in units of ink colors, and
- first calculating means (204) for obtaining set values of the opening amounts of said ink fountain keys of the respective ink colors in accordance with image area ratios of respective areas, corresponding to said ink fountain keys, of said plate of the respective ink colors by following a relationship, preset to be common to the respective ink colors, between an image area ratio and the opening amounts of said ink fountain keys.
13. An apparatus according to claim 12, further comprising overwriting means (201, 202) for overwriting the correction values of the opening amounts of said ink fountain keys in units of ink colors.
14. An apparatus according to claim 13, wherein said overwriting means comprises
- second calculating means (201) for obtaining reference opening amounts of said ink fountain keys of the respective ink colors, prior to start of actual printing, by following the relationship, preset to be common to the respective ink colors, between the image area ratio and the opening amounts of said ink fountain keys, and
- setting means (202) for setting correction values of the reference opening amounts of said ink fountain keys of the respective ink colors output from said second calculating means on the basis of measured densities in units of ink colors of a printing sample printed by using testing plates of the respective ink colors having the same image area ratio.
15. An ink supply amount adjusting apparatus for a multicolor printing press which performs multicolor printing with a plurality of printing units (9-1 - 9-4) provided to correspond to a plurality of ink colors, each of said printing units having an ink fountain (1) for storing ink (2), an ink fountain roller (3) to which said ink is supplied from said ink fountain, a plurality of ink fountain keys (4) aligned in an axial direction of said ink fountain roller to adjust an amount of ink to be supplied from said ink fountain to said ink fountain roller, and an ink roller group (6) for supplying said ink to a plate (7) in an amount adjusted in accordance with a feed rate of said ink fountain roller, characterized by comprising
- setting means (302) for setting correction values of feed rates of said ink fountain rollers in units of ink colors, and
- first calculating means (303) for correcting a reference feed rate of said ink fountain roller preset to be common to the ink colors by using the correction values obtained by said setting means, thereby obtaining set values of the feed rates of said ink fountain rollers of the respective ink colors.
16. An apparatus according to claim 15, further comprising overwriting means for overwriting the correction values of the feed rates of said ink fountain rollers in units of ink colors.
17. An apparatus according to claim 15 or 16, further comprising
- second calculating means (103) for obtaining reference opening amounts of said ink fountain keys of the respective ink colors in accordance with image area ratios of respective areas, corresponding to said ink fountain keys, of said plate by following a relationship, preset to be common to the respective ink colors, between an image area ratio and the opening amounts of said ink fountain keys, and
- third calculating means (104) for uniformly correcting the reference opening amounts of said ink fountain keys of the respective ink colors output from said second calculating means with correction values preset in units of ink colors,

thereby obtaining set values of the opening amounts of said ink fountain keys of the respective ink colors.

18. An apparatus according to any one of claims 15 to 17, further comprising

correcting means (203) for correcting origin positions of the opening amounts of said ink fountain keys of the respective ink colors with the correction values of the opening amounts of said ink fountain keys preset in units of ink colors, and  
second calculating means (204) for obtaining set values of the opening amounts of said ink fountain keys of the respective ink colors in accordance with image area ratios of respective areas, corresponding to said ink fountain keys of said plate of the respective ink colors by following a relationship, preset to be common to the respective ink colors, between image area ratios and the opening amounts of said ink fountain keys.

25

30

35

40

45

50

55




FIG. 1




FIG. 2






FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C





FIG. 6






FIG. 8




FIG. 9




FIG. 10




FIG. 11






FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18

FIG. 19A




FIG. 19B





FIG. 19C





European Patent  
Office

## EUROPEAN SEARCH REPORT

Application Number  
EP 00 25 0295

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	GB 2 080 201 A (MILLER JOHANNISBERG DRUCKMASCH) 3 February 1982 (1982-02-03)  * the whole document *	1-3,5,6,9,10,12,13,15,16	841F31/04 841F31/12
X	EP 0 668 162 A (KOMORI PRINTING MACH) 23 August 1995 (1995-08-23) * the whole document *	1-3,9,10,12,13	
A	EP 0 085 750 A (ROLAND MAN DRUCKMASCH) 17 August 1983 (1983-08-17)		
A	US 4 864 930 A (RUNYAN ET AL.) 12 September 1989 (1989-09-12)		
A	DE 37 08 652 A (GRAPHO METRONIC GMBH & CO) 29 September 1988 (1988-09-29)		
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			B41F
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 14 December 2000	Examiner DIAZ-MAROTO, V
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 03 82 (PSC001)



ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.

EP 00 25 0295

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

14-12-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2080201 A	03-02-1982	DE 3028025 A	11-02-1982
		CA 1168109 A	29-05-1984
		CH 652076 A	31-10-1985
		CS 229663 B	18-06-1984
		DD 156170 A	04-08-1982
		FR 2487259 A	29-01-1982
		JP 1698373 C	28-09-1992
		JP 3058913 B	06-09-1991
		JP 57032967 A	22-02-1982
		SE 437351 B	25-02-1985
		SE 8009111 A	25-01-1982
		US 4784060 A	15-11-1988
EP 0668162 A	23-08-1995	JP 7227958 A	29-08-1995
		AT 158233 T	15-10-1997
		DE 69500704 D	23-10-1997
		DE 69500704 T	26-02-1998
		US 5524542 A	11-06-1996
EP 0085750 A	17-08-1983	DE 3204501 C	27-10-1983
		JP 58147368 A	02-09-1983
US 4864930 A	12-09-1989	JP 2524114 B	14-08-1996
		JP 62053838 A	09-03-1987
		JP 6064149 A	08-03-1994
		JP 2652836 B	10-09-1997
		JP 6064150 A	08-03-1994
		US 5052298 A	01-10-1991
DE 3708652 A	29-09-1988	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82